

AP-103 WET & LOOK

ANTI STAIN PROTECTIVE IMREGNATOR, ENHANCER



MARBLES

GRANITES

CEMENT

POROUS STONES

LIMESTONES

NATURAL STONE

SANDSTONES

PACKAGING : 0.75 L, 5L, 20L

COVERAGE

4 - 12 m²/L with 0,75L : 3 - 9 m² depending on the absorbency of the surface.

TECHNICAL INFORMATION

Form:	Liquid
Color:	Transparent
Odor:	Mild
Density at 20 °C:	1 g/cm ³
pH:	Not applicable
Flash point:	100 °C
Freezing point:	-10 °C

Store at temperatures from 3 °C to 30 °C.

ISO EN 16301 - Determination of sensitivity to accidental staining. (Category 1, no change)

ISO EN 1925 – Determination of water absorption coefficient through capillarity (98% reduction in water absorption)

DESCRIPTION

Impregnating sealer which enhances the natural colourings of stones. It seals and protects polished and unpolished marbles and granites, all porous rocks natural and artificial, from oil, water, mustard stains, coffee, etc. Minimizes the absorbency of the surface in water and oil, while at the same time it gives the appearance of wet surface. It is able to withstand the test of time, and extreme weather conditions. It is suitable for both indoor and outdoor use. It does not create a film and it's non yellowing.

APPLICATION

Please read the label carefully. Before each use apply the product on a small surface to determine the ease of application and if you have the desired results. Make sure the surface is clean and has no waxes or other coatings.

Always make sure the application space is sufficiently ventilated. On a well cleaned and dry surface apply the liquid without dilution with a brush, roller or spray. Apply one or more coatings, while spreading any excess liquid.

The second coating should be applied as long as the surface is still wet. Any residues can be removed after the surface is dry. In case that any residues remain for a longer period of time on the surface, they can be removed with a cloth slightly wet with the liquid.

The surface can be used after six hours provided that the surface is completely dried. Maximum protection is obtained after the full curing of the product, for which 24-48 hours are required depending on the humidity of the environment. The tools can be cleaned with white spirit.

INFORMATION ON STORAGE AND HANDLING

Harmful, do not inhale any vapors
Flammable. It can cause lung damage if swallowed.

Prolonged exposure may cause skin dryness or cracking. Inhalation of vapours may cause drowsiness and dizziness.

SAFETY INSTRUCTIONS

Keep out of the reach of children. Away from sources of ignition - No smoking. Take precautionary measures against electrostatic discharges.

If swallowed, do not induce vomiting: Seek medical advice immediately and show this container or label.

APOLLON PSALTIRAS SUCCESSORS

Od. Elyti 92 Ano Liosia 13 341 • Tel: 801 112 765 566 • e-mail: info@apollon.com.gr • www.apollon.com.gr